

4MP Solar 4G Pan-Tilt ATC Camera



Product Features;

- 4MP (2560 X 1440) Resolution.
- All Time Color Images with Dual Light Technology.
- Full Duplex Audio Intercom (Built-in High Sensitivity Mic & Speaker).
- Built-in PIR Sensor.
- Supports 256Gb Micro SD-Card and Cloud Storage (Optional).
- Supports 10X Digital Zoom.
- Built-in Rechargeable 15600mAh Lithium Battery.
- Comes with 7 Watt Solar Panel.
- Smart Motion Detection, Human Detection & Human Tracking.
- Mobile Notification on Human & Motion Detection.
- Customized Pre-Recorded Voice Alarm.
- QR Code Scanning for Network Connection.
- Monitoring on Mobile Application (Wiseline HD/ EseeCloud).
- IP66 Dust & Water Resistant.



Motion Detection



Humanoid Detection



Dual Light



2-Way Audio

Technical Specification	
Product Model:	W4GS-4030A-DL
Image Sensor :	1/2.8" CMOS Sensor
Resolution:	4MP (2560 X 1440)
Lens:	4mm Fixed
IR LED:	6 IR Array, IR Distance: 30 Mtrs
White LED:	6 White Array, White LED Distance: 20 Mtrs
Min Illumination:	Color: 0.01 Lux, Black & White: 0.001 Lux
Day & Night:	IR-cut Auto ICR
Light Mode:	Full Color / Infrared
Pan-Tilt Angle:	Pan: 0°~270°, Tilt: 0°~90°, Horizontal Speed 20°/S, Vertical Speed: 10°/S
Video Streaming:	Main Stream: 2560 X 1440@15 fps
Sub Stream:	640x360@15 fps
Audio Input/Output:	Two way audio, Built in microphone and speakers
Audio Compression Standard:	AAC/ G711A
Zoom:	10x Digital
DNR:	3D Digital Noise Reduction
White Balance:	Auto
WDR:	D-WDR
Mirror/Flip:	On / Off
Electronic Shutter:	Auto
On Screen Display (OSD):	Date, Time, & Title
AI Features:	Motion Detection, Human Detection, Human Tracking.
Privacy Zone:	Supports 4 Zone
Monitoring:	Andriod, iOS, Windows (Wiseline HD/ EseeCloud)
Storage:	Support Micro SD Card upto 256GB & Cloud Storage (Optional)
PIR Detection:	10 meters distance, 120 degrees cover
Connection Mode:	4G Sim Network
Slots:	4G Sim Card / Micro SD Card
4G Frequency Band:	FDD-LTE: B1/B3/B5/B8; TDD-LTE: B34/B38/B39/B40/B41
Battery:	Built-in 15600mAh Rechargeable battery
Solar Panel:	7 Watt
Power Input:	DC: 5V/2A (Type-C)
Power Consumption:	≤8W
Working Temperature / Humidity:	0-50° C, RH Less than 95% (No Condensation)
Storage Temperature / Humidity:	-20° C to 60° C / 20% to 90% RH
Housing Type:	IP66, Plastic.