

## 3MP 4G Bullet All Time Color Camera



### Product Features;

- 3MP High Resolution.
- All Time Color Images with Smart Dual Light Technology.
- Full Duplex Audio Intercom (Built-in High Sensitivity Mic & Speaker).
- Supports 256Gb Micro SD-Card and Cloud Storage (Optional).
- Supports 10X Digital Zoom.
- Smart Motion Detection and Human Detection.
- Mobile Notification on Human & Motion Detection.
- Customized Pre-Recorded Voice Alarm.
- QR Code Scanning for Network Connection.
- Monitoring on Mobile Application (Wiseline HD/ EseeCloud).
- IP66 Dust & Water Resistant.



Motion Detection



Humanoid Detection



Dual Light



2-Way Audio

<b>Technical Specification</b>	
Product Model:	W4GB-3030A-DL
Image Sensor :	1/2.8" CMOS Sensor
Resolution:	3MP (2304 x 1296)
Lens:	4mm Fixed
IR LED:	4 IR Array, IR Distance: 30 Mtrs
White LED:	4 White Array, White LED Distance: 20 Mtrs
Min Illumination:	Color: 0.01 Lux, Black & White: 0.001 Lux
Day & Night:	IR-cut Auto ICR
Light Mode:	Full Color / Infrared / Intelligent
Viewing Angle:	Horizontal: 75°, Vertical: 59°, Diagonal: 88°
Video Streaming:	Main Stream: 2304x1296@15 fps
Sub Stream:	800x448@15 fps
Audio Input/Output:	Two way audio, Built in microphone and speakers
Audio Compression Standard:	AAC
Zoom:	10x Digital
DNR:	3D Digital Noise Reduction
White Balance:	Auto
WDR:	D-WDR
Mirror/Flip:	On / Off
Electronic Shutter:	Auto
On Screen Display (OSD):	Date, Time, & Title
AI Features:	Motion Detection, Human Detection.
Privacy Zone:	Supports 4 Zone
Monitoring:	Andriod, iOS, Windows (Wiseline HD/ EseeCloud)
Storage:	Support Micro SD Card upto 256GB & Cloud Storage (Optional)
Communication Protocol:	Private N1/RTMP
Connection Mode:	4G Sim Network
Slots:	4G Sim Card / Micro SD Card
4G Frequency Band:	FDD-LTE: B1/B3/B5/B8; TDD-LTE: B34/B38/B39/B40/B41
Connectors:	DC Power Input & Reset Button
Power Input:	DC: 12V/1A (DC 2.1mm Connector)
Power Consumption:	≤3W
Working Temperature / Humidity:	0-50° C, RH Less than 95% (No Condensation)
Storage Temperature / Humidity:	-20° C to 60° C / 20% to 90% RH
Housing Type:	IP66, Plastic.