



3+3MP 4G Mini PT Solar Linkage Camera.

W4GS-3030-L-AVV4G SIM
Support256GB
SD Card3+3MP
ResolutionBattery
BackupAuto Human
TrackingIP66
RatingHigh Quality
Solar PanelCloud
RecordingLocation
Presets

Features:

- 3+3MP 4G Mini PT Solar Linkage Camera.
- 4MM+4MM Fixed Lens.
- PT Horizontal & Vertical Movement Range: Pan 266°, Tilt 90°.
- Dual monitoring. One camera for Fixed monitoring, One camera for PT detailed monitoring.
- Built-in high-sensitivity Mic. and Speaker For Full Duplex Audio Intercom.
- Support 10X Digital Zoom.
- Supports 6 preset points favourite locations.
- Unique Full Color & IR Night Vision Modes.
- Micro SD Card Up to 256GB & Cloud Storage (Optional).
- 4G Connection, QR code camera configuration with mobile/PC.
- Built-in Battery: 18000 mAh rechargeable lithium battery with 7 Watt Solar Panel.
- Built-in PIR Sensor.
- Area motion detection, Humanoid detection, Push Realtime Notification on the application.
- Support monitoring : Pc / Mobile on EseeCloud.
- Compression : H.264/H.265

Technical Specifications:

Image Sensor Resolution Lens	1/2.8" 3MP+3MP HD CMOS Dual Sensor 2304 x 2592 Bullet: 4mm fixed lens PT Dome: 4mm fixed lens
IR LEDs	Bullet : 4 Pcs PT Dome : 4 Pcs
Infrared IR Distance	>30 Meters
White LEDs	Bullet : 4 Pcs PT Dome: 4 Pcs
White LEDs Distance	>20 Meters
Minimum Illumination	Color : 0.001 Lux, BW : 0 Lux
Day & Night Mode	IR / Full Color
S/N Ratio	> 39.1 dB
White Balance	Auto
3D-DNR	Auto
Mirror/Flip	On / Off
Video Streaming	Mainstream: 2304 x 2592@15fps Substream: 800 x 896@15fps
AI Features	Human Detection Motion Detection Human Tracking
Audio Streaming	AAC/G711A
Audio IN	Built in MIC
Audio OUT	Built in Speaker
TF /SD Card	Support Max 256GB
Slots	Nano Sim Card Slot & Micro SD Card Slot
Battery	Built-in 18000mAh Rechargeable battery
Solar Panel	7 Watt
PIR Detection	10 meters distance, 120 degrees cover
Connection Mode	4G Network
Light Mode	LED Flash; 4G Network not Connected LED Continue ON; 4G Network Connected
Power Input	DC Input 5V – 2A [C-type Connector]
Thunder Prevention	Standard IEC61000-4-5
Power Consumption	≤15W
Operation Temperature/Humidity	-10°C to +50°C / 30% to 80% RH
Storage Temperature/Humidity	-20°C to +60°C / 20% to 90% RH
Dimension	185 x155 x 210mm (L×W×H)
Housing Type	Plastic Housing
Weight Net	0.900Kg
Weight Gross	1.8Kg