



## WAB-2020A-L28

## **Features**

1/2.9" CMOS Image sensor 3.6mm fixed lens 2MP@25/30fps  $0.01Lux@(F1.2,AGC\ ON)$  ,  $0LUX\ with\ IR$ Built-in microphone Support 3D DNR and digital WDR Support UTC



Image Sensor	1/2.9 " CMOS Image Sensor
Resolution	2MP
Lens	M12 3.6mm fixed lens
System	PAL/NTSC
LED	2 New Gen. Array LED
IR Range	20 Meters
Video Output	TVI/AHD/CVI/CVBS output
Minimum Illumination	0.01Lux@(F1.2,AGC ON) ,0LUX with IR
Gain Control (AGC)	Auto
Shutter	Auto
White Balance	ATW / MWB
D/N	AUTO/COLOR/B/W
Audio	Built-in Microphone with Coaxial Audio
Backlight Compensation	Support
Frame Rate	25/30fps@2MP
Power Input	DC Input 12V - 1A
Power Consumption	≥5W
Operation Temperature/Humidity	-10°C to +50°C / 30% to 80% RH
Storage Temperature/Humidity	-20°C to +60°C / 20% to 90% RH
Dimension	H66xW70xL197
Housing type	Plastic Bullet, IP66
Weight Net	0.340Kg
Weight Gross	0.460Kg



