

5MP Dual-Light 50Mtr Network Bullet Audio Camera

WNO-5050A-DLS

This smart network bullet camera comes with Dual Light Technology & Digital Wide Dynamic Range (dWDR) to ensure clarity even when there's both dark and light areas in the scene. It offers Dual Audio function with in-built Microphone & Speaker. Furthermore, this elegant, easy-to-install, IP67 rated camera comes with in-built Human Detection Algorithm.

- > **Excellent image quality in 5MP resolution.**
- > **Advanced and elegant design.**
- > **dWDR, Dual-Light, Dual-Audio.**
- > **Support human detection by default.**
- > **Night vision range of upto 50mtrs.**

Basic Parameter	
Smart Function	Human detection
Image Sensor	1/2.7", 5MP low illumination CMOS sensor
Effective Pixels	5MP (2592*1904) @20fps
Min. Illumination	Color: 0.003Lux (F1.6), 0Lux with light/ IR
Lens	Fixed lens 6mm, F1.6.
IR Distance	8 pcs Dual-Light LEDs, night vision upto 50M
Noise Reduction	3D noise reduction
WDR	D-WDR
Mirror	Off/horizontal mirror/vertical mirror/180° flip
Image Setting	Brightness, contrast, sharpness, saturation, chroma
Human Detection	
Responding Speed	≤1s
Maximum Detection Frame Rate	5fps/s
Detection Area	Support specified area, default full screen
Shielded Area	Support 4 areas setting
Upload Method	Upload it under private protocol
Trigger Method	Video trigger
Video and Audio Coding	
Encoding Format	S.265/H.265/H.264
Coding Characteristics	Main stream: 5MP (2592*1904) @ 20FPS, 4MP (2560*1440) @ 20fps, 3MP (2304*1296) @ 20fps, 2MP (1920*1080) @ 25fps. Sub-stream: D1 (720*576), VGA (640*480), Q720P (640*360), CIF (352*288), QVGA (320*240)
Video Bit Rate	Fixed code rate, variable code rate(main stream:160Kbps-4000kbps)
Video Type	Composited stream/video stream
Audio Coding Standard	G.711u/ G.711A 64Kbps

Network Function	
Network Interface	1*RJ45 10M/100M self-adaptive LAN port
Network Protocol	TCP/IP, UDP, HTTP, HTTPS, DHCP, RTSP, DDNS, NTP, PPPOE, UPNP, SMTP, P2P.
Interface Protocol	ONVIF
Port	
Network Interface	RJ45 10M/100M network adaptive
POE	Yes
Audio	Built-in Microphone and Speaker for 2-Way Audio Intercom
SD card	Optional
General	
Operation T/H	- 20°C ~ 55°C / 0 % -90 %
Waterproof	IP67
Housing Material	Metal
Power Supply	DC12V / PoE

Dimensions;

